

WHAT IS CLAIMED IS:

1. A ratchet wrench, comprising:

a wrench body having a hole and a chamber communicated with the hole;

5 a ratchet wheel rotatably mounted in the hole of the wrench body and having an annular teeth portion at an outer surface thereof and a polygonal hole at a center thereof;

a ring member mounted in the hole of the wrench body to restrain the ratchet wheel and having a predetermined color that is different from a color of the wrench
10 body and visible from outside of the ratchet wrench;

a pawl received in the chamber of the wrench body for meshing the teeth portion of the ratchet wheel, and

a spring having two ends respectively stopped at the wrench body and the pawl.

15

2. The ratchet wrench as defined in claim 1, wherein the ring member has an annular slot at an outer surface thereof in which a C-ring is mounted; said C-ring being stopped at a wall of the hold of the wrench body.

20 3. The ratchet wrench as defined in claim 1, wherein the wrench body has a sign indicating the size of the wrench.

4. A ratchet wrench, comprising:

a wrench body having a hole and a chamber communicated with the hole;

25 a ratchet wheel rotatably mounted in the hole of the wrench body and having

an annular teeth portion at an outer surface thereof and a polygonal hole at a center thereof;

a ring member mounted in the hole of the wrench body to restrain the ratchet wheel;

5 an identification layer disposed on the ring member and having a predetermined color that is different from a color of the wrench body and visible from outside of the ratchet wrench;

a pawl received in the chamber of the wrench body for meshing the teeth portion of the ratchet wheel, and

10 a spring having two ends respectively stopped at the wrench body and the pawl.

5. The ratchet wrench as defined in claim 4, wherein the identification layer is a coating layer on the ring member by printing, painting or plating.

15

6. The ratchet wrench as defined in claim 4, wherein the identification layer is a film attached on the ring member.

7. The ratchet wrench as defined in claim 4, wherein the ring member is
20 integrally formed at an end of the ratchet wheel; the ratchet wheel has an annular slot at an outer surface of the other end thereof in which a C-ring is mounted; said C-ring being stopped at a wall of the hold of the wrench body.